



CETO

WALL LIGHT - OFFSET

Ceto captures the variation and rippling of the surface of the ocean. Each piece reflects a unique pattern, emitting a delicate luminosity, highlighting the presence of the sea. This sculptural luminaire is available in a selection of mouth-blown glass finishes combined with a highly refined machined aluminium body available in a black and champagne anodised finish. The Ceto Wall Light reflects the shadows of the glass against the wall, replicating the natural flow and movement of water.

AVAILABLE FINISHES



TECHNICAL

MATERIAL	ANODISED ALUMINIUM, GLASS
LOW VOLTAGE LED (220-240V REGIONS)	<p>SELV 60V (WITH EXTERNAL DRIVER) 2-4W LED MODULE, WATTAGE WILL VARY SLIGHTLY DEPENDING ON CETO CONFIGURATION. 300-380 LUMEN RANGE PER LIGHT SOURCE. 3000K WARM WHITE.</p> <p>DIMMING OPTIONS:</p> <ul style="list-style-type: none"> · PHASE - DIMMING RANGE 5 - 100%. · DALI - DIMMING RANGE 1 - 100%. · 1-10V - DIMMING RANGE 5 - 100%. · 0-10V - NOT COMPATIBLE. <p>IF THE WALL CAVITY CANNOT HOUSE THE DRIVER PLEASE CONTACT THE STUDIO FOR FURTHER OPTIONS.</p>
120V LED (100-120V REGIONS)	<p>4W AC LED MODULE 380 LUMEN PER LIGHT SOURCE. 3000K WARM WHITE, DIMMABLE. DRIVER NOT REQUIRED, DIRECT MAINS VOLTAGE.</p> <p>DIMMING OPTIONS:</p> <ul style="list-style-type: none"> · PHASE - DIMMING RANGE 5 - 100%. · DALI - NON-DIMMABLE, ON/OFF FUNCTIONALITY ONLY VIA DALI SWITCH. · 1-10V - NOT COMPATIBLE. · 0-10V - NOT COMPATIBLE.

CONT.	FOR OPTIMAL DIMMING PERFORMANCE WE RECOMMEND SOURCING A ROTARY OR PUSH BUTTON DIMMER WITH ADJUSTMENT DIAL CAPABLE OF SETTING THE DIMMING RANGE OF THE FIXTURE.
MOUNTING	<p>PLEASE CONTACT OUR STUDIO FOR FURTHER INFORMATION REGARDING MOST SUITABLE LAMPING TECHNOLOGY FOR YOUR SPECIFIC PROJECT/REGION.</p> <p>WALL MOUNT BODY Ø100MM / 3.9". TO ENSURE CORRECT COVERAGE OVER 4" JUNCTION BOXES AN ADDITIONAL Ø120MM / 4.7" COVER PLATE IS SUPPLIED FOR 100-120V REGIONS. MOUNTING HOLES DESIGNED TO SUIT STANDARD 4" JUNCTION BOXES.</p>
LED LIFESPAN	50,000 HRS
CERTIFICATION	<p>AS/NZS - 60598.2.1 EN - 60598.2.1 UL 1598, CSA C22.2#250.0</p>
IP RATING	IP20 - FOR INDOOR USE ONLY
PRODUCT CODES SKU	<p>EG. CWL1.G-BLK.A-BLK = CETO WALL LIGHT WITH OFFSET MOUNT IN BLACK GLASS WITH A BLACK ANODISED BODY</p>

CWL1-G-XXX.A-XXX	CETO WALL LIGHT WITH OFFSET MOUNT
CWL2-G-XXX.A-XXX	CETO DOUBLE WALL LIGHT WITH OFFSET MOUNT

FINISHES FOR ALL VARIATIONS:	<p>GLASS: FROSTED BLACK (G-FBK) BLACK (G-BLK) CLEAR (G-CLR) WHITE (G-WHT)</p> <p>BODY: BLACK ANODISED (A-BLK) CHAMPAGNE ANODISED (A-CHM)</p>
------------------------------	--

DIMENSIONS	VARIOUS - SEE DIMENSIONS ON FOLLOWING PAGE*
------------	---

WEIGHT	CWL1 - 2KG / 4.4LB CWL2 - 4KG / 9LB
--------	--

PACKAGING	CWL1 - L 58CM W 35CM H 25CM / L 20" W 20" H 9.8" CWL2 - L 50CM W 50CM H 25CM / L 20" W 20" H 9.8"
-----------	--

PACKAGING WEIGHT	CWL1 - 2KG / 4.4LB CWL2 - 4KG / 9LB
------------------	--

DIMENSIONS



CWL1
W 200 H 400 D 107
W 7.9" H 15.8" D 4.2"



CWL2
W 200 H 650 D 107
W 7.9" H 25.6" D 4.2"