

CETO

PENDANT

Ceto captures the variation and rippling of the surface of the ocean. Each piece reflects a unique pattern, emitting a delicate luminosity, highlighting the presence of the sea. This sculptural luminaire is available in a selection of mouth-blown glass finishes combined with a highly refined machined aluminium body available in a black and champagne anodised finish. The Ceto Pendant Light softly illuminates a space, providing a tranquil calming light.

AVAILABLE FINISHES















FROSTED BLACK

CLEAR GLASS

TECHNICAL

(220-240V REGIONS)

MATERIAL ANODISED ALUMINIUM, GLASS LOW VOLTAGE LED SELV 60V (WITH EXTERNAL DRIVER)

> 2-4W LED MODULE, WATTAGE WILL VARY SLIGHTLY DEPENDING ON CETO CONFIGURATION. 300-380 LUMEN RANGE PER LIGHT SOURCE, 3000K WARM WHITE.

DIMMING OPTIONS:

PHASE - DIMMING RANGE 5 - 100% DALI - DIMMING RANGE 1 - 100%

IF THE CEILING CAVITY CANNOT HOUSE THE DRIVER PLEASE CONTACT THE STUDIO FOR FURTHER OPTIONS.

120V L FD (100-120V REGIONS) 4W AC LED MODULE (INTEGRATED DRIVER) 380 LUMEN PER LIGHT SOURCE. 3000K WARM WHITE, DIMMABLE. DRIVER NOT REQUIRED, DIRECT MAINS VOLTAGE.

DIMMING OPTIONS:

PHASE - DIMMING RANGE 5 - 100%.

DALI - NON-DIMMABLE, ON/OFF FUNCTIONALITY ONLY VIA DALI SWITCH (NOT SUPPLIED).

ALL US AND CANADIAN ORDERS COME SUPPLIED WITH 120V COMPONENTRY CERTIFIED FOR USE IN THESE

FOR OPTIMAL DIMMING PERFORMANCE WE RECOMMEND SOURCING A ROTARY OR PUSH BUTTON DIMMER WITH ADJUSTMENT DIAL CAPABLE OF SETTING THE DIMMING RANGE OF THE FIXTURE.

PLEASE CONTACT OUR STUDIO FOR FURTHER INFORMATION REGARDING MOST SUITABLE LAMPING TECHNOLOGY FOR YOUR SPECIFIC PROJECT/REGION.

LED LIFESPAN 50,000 HRS IP RATING IP20 - FOR INDOOR USE ONLY

CERTIFICATION AU/NZ AS/NZS 60598.1, 60598.2.1 EN 60598.1, 60598.2.1 US/CAN ETL/UL 1598, CSA C22.2#250.0

2M / 6.6' SUPPLIED DOUBLE INSULATED CABLE CORD

COVERED BY A DURABLE BLACK OR WHITE CLOTH COVER. LONGER LENGTHS AVAILABLE UPON REQUEST.

CANOPY VARIOUS - SEE CANOPY OPTIONS ON FOLLOWING PAGE

PRODUCT CODES SKU EG. CP1.G-BLK.A-BLK = CETO PENDANT - SINGLE IN BLACK GLASS WITH A BLACK ANODISED BODY

CP1-G-XXX.A-XXX CETO PENDANT- SINGLE CP3-G-XXX.A-XXX CETO PENDANT- TRIPLE CETO PENDANT- SEVEN CP7-G-XXX.A-XXX

FINISHES: GLASS: FROSTED BLACK (G-FBK)

BLACK (G-BLK) CLEAR (G-CLR) WHITE (G-WHT) BODY: BLACK ANODISED (A-BLK)

CHAMPAGNE ANODISED (A-CHM)

DIMENSIONS VARIOUS - SEE DIMENSIONS ON FOLLOWING PAGE*

1.5KG / 3LB WEIGHT CP1 -CP3 -4.5KG / 10LB CP7 -7.5KG / 23LB

PACKAGING L25CM W25CM H25CM/L9.8" W9.8" H9.8"

L50CM W50CM H25CM/L20" W20" H9.8" 2 X L 50CM W 50CM H 25CM / L 20" W 20" H 9.8"

PACKAGING WEIGHT CP1 -2KG / 4.4LB

CP3 - 5KG / 11LB 2 X 4KG / 8.8LB



323.904.1200 www.twentieth.net

DIMENSIONS



CP1 Ø 200 H 105 Ø 7.9" H 4.1"



CP3 Ø410 H120 Ø16.1" H4.7"



CP7 Ø 590 H130 Ø23.2" H 5.1" *MINIMUM DROP HEIGHT REQUIREMENTS - SEE BELOW.

* CP7 MINIMUM DROP HEIGHT WITH SUPPLIED CABLE SUSPENSION TUBE IS 1050MM / 3'5", ALTERNATIVELY REMOVE THE CABLE SUSPENSION TUBE AND HANG THE FIXTURE AT 700MM / 2'4" TO ENSURE CORRECT BALANCE BETWEEN PENDANTS.

AVAILABLE CANOPIES

ALL ROSS GARDAM CEILING MOUNTED FIXTURES COME SUPPLIED WITH A CEILING CANOPY UNLESS OTHERWISE SPECIFIED. EACH CANOPY INCLUDES ELECTRICAL CONNECTORS, EARTH WIRE AND CABLE RETENTION TO CONNECT TO MAINS POWER. THE BELOW IMAGES DEPICT THE CEILING CANOPIES AVAILABLE WITH EACH FIXTURE TYPE. IF NO CANOPY IS SELECTED, THE STANDARD CANOPY (NON US/CAN REGION) OR LARGE CANOPY (US/CAN) WILL BE SUPPLIED.

SINGLE PENDANT



STANDARD SINGLE PENDANT CANOPY CAN.ST.120.SP.X-XXX

Ø120 X 30MM / 4.7" X 1.2"

DRIVER HOUSED IN CEILING



LARGE SINGLE PENDANT CANOPY CAN.ST.170.SP.X-XXX

Ø170 X 40MM / 6.7" X 1.6"

DRIVER HOUSED IN CANOPY



SLIM SINGLE PENDANT CANOPY CAN.SL.SP.X-XXX

Ø120 X 7MM / 4.7" X 0.3"

DRIVER HOUSED IN CEILING



PUCK SINGLE PENDANT CANOPY CAN.PK.SP.X-XXX

Ø50 X 65MM / 2" X 2.6"

DRIVER HOUSED IN CEILING

CLUSTER PENDANT - 3



STANDARD CLUSTER PENDANT - 3 CAN.ST.120.SP.X-XXX

Ø120 X 30MM / 4.7" X 1.2"

DRIVER HOUSED IN CEILING



LARGE CLUSTER PENDANT - 3 CAN.ST.170.SP.X-XXX

Ø170 X 40MM / 6.7" X 1.6"

DRIVER HOUSED IN CANOPY

CLUSTER PENDANT - 7



STANDARD CLUSTER PENDANT - 7 CAN.ST.120.SP.X-XXX

Ø120 X 30MM / 4.7" X 1.2"

DRIVER HOUSED IN CEILING



LARGE CLUSTER PENDANT - 7 CAN.ST.170SP.X-XXX

Ø170 X 40MM / 6.7" X 1.6"

DRIVER HOUSED IN CANOPY

TECHNICAL

MATERIAL ANODISED ALUMINIUM







CHAMPAGI

CANOPY FINISH ANODISED BLACK (A-BLK)

ANODISED CHAMPAGNE (A-CHM)

PRODUCT SKU CODE

EG. CAN.ST.120.SP.A-CHM = STANDARD SINGLE PENDANT CANOPY IN CHAMPAGNE ANODISED FINISH

