




## OAK PENDANT

Oak is a sustainably sourced timber pendant light which emits a delicate luminance. Each Oak Pendant Light shade is hand crafted and defined by the grain of the oak selected. The body of the light is accentuated by the intersecting hole which defines its unique form.

The Oak pendant is available in two sizes and three finishes.

### AVAILABLE FINISHES



NATURAL OAK HARDWOOD LIMED OAK HARDWOOD BLACK OAK HARDWOOD

### TECHNICAL


MATERIAL	OAK HARDWOOD OR BLACKWOOD HARDWOOD
LAMPING	STANDARD: 8.5W E27 LED, 820 LM 3000K WARM WHITE, DIMMABLE LARGE: 13W E27, 1521 LM 2700K WARM WHITE, DIMMABLE  SUPPLIED WITH AUS/NZ SALES (220-240V) ONLY (120V) E26 LAMP HOLDER SUPPLIED FOR NORTH AMERICA/CANADA
LED LIFESPAN	15,000 HRS
CONTROL	PHASE CONTROL / NETWORK CONTROL DIMMABLE DIMMING RANGE 10 - 100%. FOR OPTIMAL DIMMING PERFORMANCE WE RECOMMEND SOURCING A ROTARY OR PUSH BUTTON DIMMER WITH AN ADJUSTMENT DIAL CAPABLE OF SETTING THE DIMMING RANGE OF THE FIXTURE.
CANOPY	VARIOUS - SEE CANOPY OPTIONS ON FOLLOWING PAGE
CORD	2M / 7" (STANDARD) OR 3M / 10" (LARGE) BLACK CLOTH AND SUSPENSION WIRE NOTE: LONGER LENGTHS AVAILABLE UPON REQUEST
IP RATING	IP20 - FOR INDOOR USE ONLY

CERTIFICATION	AU/NZ AS/NZS 60598.1, 60598.2.1 EU EN 60598.1, 60598.2.1 US/CAN ETL/UL 1598, CSA C22.2#250.0
PRODUCT CODES SKU	EG. OP.S.H-OAK = OAK STANDARD PENDANT IN NATURAL OAK HARDWOOD
OP.S.H-XXX	OAK STANDARD PENDANT
OP.L.H-XXX	OAK LARGE PENDANT
FINISHES FOR ALL VARIATIONS:	NATURAL OAK HARDWOOD (H-OAK), LIMED STAINED OAK HARDWOOD (H-LIM) AND BLACK STAINED OAK HARDWOOD (H-BLK)
DIMENSIONS	Ø215X260MM / Ø 8.5X10.3" Ø352X425MM / Ø 13.8X16.7"
WEIGHT	4 / 10KG 15 / 33LB
PACKAGING	30X30X30CM / 45X45X47CM 11.8X11.8X11.8" / 17.7X17.7X18.5"
PACKAGING WEIGHT	5KG / 11LB 18KG / 39.7LB

### DIMENSIONS



OPS  
Ø215 H260  
Ø8.5" H10.3"



OPL  
Ø352 H425  
Ø13.8" H16.7"

### AVAILABLE CANOPIES

ALL ROSS GARDAM CEILING MOUNTED FIXTURES COME SUPPLIED WITH A CEILING CANOPY UNLESS OTHERWISE SPECIFIED. EACH CANOPY INCLUDES ELECTRICAL CONNECTORS, EARTH WIRE AND CABLE RETENTION TO CONNECT TO MAINS POWER. THE BELOW IMAGES DEPICT THE CEILING CANOPIES AVAILABLE WITH EACH FIXTURE TYPE. IF NO CANOPY IS SELECTED, THE STANDARD CANOPY WILL BE SUPPLIED.

### OAK STANDARD



STANDARD - 120MM  
SUSPENSION + FLEX CANOPY  
CAN.ST.120.SF.X-XXX  
Ø120 X 30MM / 4.7" X 1.2"



SLIM  
SUSPENSION + FLEX CANOPY  
CAN.SL.SF.X-XXX  
Ø120 X 7MM / 4.7" X 0.3"



PUCK  
SUSPENSION + FLEX CANOPY  
CAN.PK.SF.X-XXX  
Ø50 X 65MM / 2" X 2.6"

### OAK LARGE (EXTERNAL CEILING ANCHOR PROVIDED WITH CANOPY)



STANDARD - 120MM  
SINGLE PENDANT + EXTERNAL  
CEILING MOUNT CANOPY  
CAN.ST.120.SFCM.X-XXX  
Ø120 X 30MM / 4.7" X 1.2"



SLIM  
SINGLE PENDANT + EXTERNAL  
CEILING MOUNT CANOPY  
CAN.SL.SFCM.X-XXX  
Ø120 X 7MM / 4.7" X 0.3"



PUCK  
SINGLE PENDANT + EXTERNAL  
CEILING MOUNT CANOPY  
CAN.PK.SFCM.X-XXX  
Ø50 X 65MM / 2" X 2.6"

### TECHNICAL

MATERIAL	ANODISED ALUMINIUM / POWDERCOATED ALUMINIUM
	<p>BLACK ANODISED CHAMPAGNE ANODISED WHITE POWDERCOATED</p>
CANOPY FINISH	ANODISED BLACK (A-BLK) ANODISED CLEAR (A-CHM) POWDERCOATED WHITE (C-WHT)
PRODUCT CODES SKU	EG. CAN.ST.120.SF.A-CHM = STANDARD SUSPENSION + FLEX CANOPY IN CHAMPAGNE ANODISED FINISH