



VOLANT

WALL LIGHT

Volant features solid brass bars, paired with textured, tubular formed-glass elements, creating a statement luminaire. This delicate light creates an equilibrium between the different materials and offers a beautifully soft level of luminosity.

Volant’s architectural nature allow the fixture to span across a plethora of interior spaces. The solid brass bars are individually machined with the luminaire defined by a white glass diffuser which is pinned in-place to the solid brass bar. Textured tubular glass elements are balanced on the same pins creating a uniquely formed illumination.

AVAILABLE FINISHES



TECHNICAL

<p>MATERIAL</p> <p>TREATED BRASS, GLASS</p>	<p>MOUNTING</p> <p>VW1 - WALL MOUNT BODY - H 330 X W 22 / H 11" X W 0.9" VW2 - WALL MOUNT BODY - H 330 X W 15.5 / H 11" X W 0.6"</p>
<p>FINISH</p> <p>ALL BRASS FRAMES ARE BRUSHED AND TREATED TO ACHIEVE THE AVAILABLE FINISH OPTIONS, THEN WAXED TO PREVENT ACCELERATED AGING.</p>	<p>TO ENSURE CORRECT COVERAGE OVER 4" JUNCTION BOXES AN ADDITIONAL MOUNTING PLATE (Ø110MM / 4.3") & COVER PLATE (250MMH X 120MMW / 9.9"H X 4.7"W) IS SUPPLIED FOR US/CAN REGIONS. MOUNTING HOLES DESIGNED TO SUIT STANDARD 4" OCTAGONAL JUNCTION BOXES. MOUNT & COVER PLATES ARE NOT SUPPLIED FOR OTHER REGIONS.</p>
<p>LAMPING</p> <p>SELV 60V (EXTERNAL DRIVER SUPPLIED) VW1 - 5.3W, 775 LUMEN, 2700K VW2 - 7.8W, 1180 LUMEN, 2700K</p>	<p>PRODUCT SKU CODE</p> <p>EG. VW2.G-FLU.BR-BRZ VOLANT DOUBLE WALL LIGHT IN FLUTED CLEAR GLASS WITH A BRONZED BRASS FRAME</p> <p>VW1.G-XXX.BR-XXX VOLANT SINGLE WALL LIGHT VW2.G-XXX.BR-XXX VOLANT DOUBLE WALL LIGHT</p>
<p>220-240V REGIONS</p> <p>DIMMING OPTIONS</p> <ul style="list-style-type: none"> · PHASE - DIMMING RANGE 5 - 100% · DALI - DIMMING RANGE 1 - 100% 	<p>FINISHES</p> <p>GLASS FROSTED BLACK (G-FBL) FLUTED (G-FLU) FROSTED FLUTED (G-FFL)</p> <p>FRAME BRUSHED BRASS (BR-NAT) BLACKENED BRASS (BR-BLK) BRONZED BRASS (BR-BRZ)</p>
<p>110-120V REGIONS</p> <p>DIMMING OPTIONS</p> <ul style="list-style-type: none"> · PHASE - DIMMING RANGE 3 - 100% · DALI - DIMMING RANGE 0.1 - 100% <p>ALL US AND CANADIAN ORDERS COME SUPPLIED WITH 120V COMPONENTRY CERTIFIED FOR USE IN THESE REGIONS.</p> <p>FOR OPTIMAL DIMMING PERFORMANCE WE RECOMMEND SOURCING A DIMMER CAPABLE OF SETTING THE DIMMING RANGE OF THE FIXTURE.</p>	<p>WEIGHT</p> <p>VW1 2KG / 4.4LB VW2 5KG / 11LB</p>
<p>LED LIFESPAN</p> <p>50,000 HRS</p>	<p>PACKAGING WEIGHT</p> <p>VW1 1X 3KG / 6.6LB VW2 1X 6KG / 13.2LB</p>
<p>IP RATING</p> <p>IP20 - FOR INDOOR USE ONLY</p>	<p>PACKAGING SIZE</p> <p>VW1 L 55CM W 26CM H 10CM / L 21.6" W 10'3" H 4" VW2 L 55CM W 34CM H 10CM / L 21.6" W 10'3" H 4"</p>
<p>CERTIFICATION</p> <p>AU/NZ AS/NZS 60598.1, 60598.2.1 EU EN 60598.1, 60598.2.1 US/CAN ETL/UL CERTIFICATION PENDING</p>	

twentieth

sales@twentieth.net
 323.904.1200
 www.twentieth.net

DIMENSIONS



VW1
W 70 H 500 D 80
W 2.8" H 1'8" D 3.2"



VW2
W 160 H 500 D 80
W 6.3" H 1'8" D 3.2"

twentieth

sales@twentieth.net
323.904.1200
www.twentieth.net