



CETO

WALL LIGHT

Ceto captures the variation and rippling of the surface of the ocean. Each piece reflects a unique pattern, emitting a delicate luminosity, highlighting the presence of the sea. This sculptural luminaire is available in a selection of mouth-blown glass finishes combined with a highly refined machined aluminium body available in a black and champagne anodised finish. The Ceto Wall Light reflects the shadows of the glass against the wall, replicating the natural flow and movement of water.

AVAILABLE FINISHES



TECHNICAL

MATERIAL	ANODISED ALUMINIUM, GLASS
LAMPING	SELV 60V (WITH EXTERNAL DRIVER) CW1 - 3.7W, 400 LM, 3000K
DIMMING OPTIONS	220-240V REGION
	PHASE - DIMMING RANGE 5 - 100%
	DALI - DIMMING RANGE 1 - 100%
	110-120V REGION
PHASE - DIMMING RANGE 3 - 100%	
DALI - DIMMING RANGE 0.1 - 100%	
	ALL US AND CANADIAN ORDERS COME SUPPLIED WITH 120V COMPONENTRY CERTIFIED FOR USE IN THESE REGIONS.
	FOR OPTIMAL DIMMING PERFORMANCE WE RECOMMEND SOURCING A DIMMER CAPABLE OF SETTING THE DIMMING RANGE OF THE FIXTURE.
DRIVER SIZE	
220 -240V	PHASE / TRIAC
	CW1 - L101 X W51 X H29 / L4.7" X W2" X H1.1"
	DALI
	CW1 - L120 X W51 X H29 / L4.7" X W2" X H1.1"
110-120V	PHASE / TRIAC
	CW1 - L75 X W35 X H26.5 / L3" X W1.4" X H1"
	DALI
	CW1 - L75 X W35 X H26.5 / L3" X W1.4" X H1"

MOUNTING	WALL MOUNT BODY Ø100MM / 3.9". FOR PROPER COVERAGE OF 4" JUNCTION BOXES, A Ø120MM / 4.7" COVER PLATE IS PROVIDED FOR US/CAN ORDERS.	
LED LIFESPAN	50,000 HRS	
CERTIFICATION	AU/NZ	AS/NZS 60598.1, 60598.2.1
	EU	EN 60598.1, 60598.2.1
	US/CAN	ETL/UL 1598, CSA C22.2#250.0
IP RATING	IP20 - FOR INDOOR USE ONLY	
SKU CODES	EG. CW1.G-BLK.A-BLK = CETO WALL LIGHT IN BLACK GLASS WITH A BLACK ANODISED CANOPY	
	CW1.G-XXX.A-XXX	CETO SINGLE WALL LIGHT
FINISHES GLASS	FROSTED BLACK (G-FBK) BLACK (G-BLK) CLEAR (G-CLR) WHITE (G-WHT)	
BODY	BLACK ANODISED (A-BLK) CHAMPAGNE ANODISED (A-CHM)	
DIMENSIONS	Ø 200 / 7.9" X D 87 / 3.4"	
PRODUCT WEIGHT	1.5KG / 3.5LB	
PACKAGING DIMENSIONS	L 250 W 250 H 250 / L 9.8" W 9.8" H 9.8"	
PACKAGING WEIGHT	1.5KG / 3.5LB	

DIMENSIONS



CW1
Ø 200 / 7.9" X D 87 / 3.4"