

MÉNE

PENDANT

Méne celebrates our sense of awe of the celestial. The pendant appears like a lunar apparition, delicately floating in mid-air. Crafted with mouth blown glass, the collection reveals the individual and unique texture of subtly illuminated glass. Méne's rippled form is the result of the studio's continual experimentations with traditional optic glass blowing techniques and innovative engineering. The result is a one of a kind glass texture within every luminaire produced.

AVAILABLE FINISHES












TECHNICAL

twentieth

MATERIAL	ANODISED ALUMINIUM, GLASS		LED LIFESPAN	50,000 HRS	
LAMPING SELV 60V (EXTERNAL DRIVER SU 8W, 1070 LM, 3000K		LIED)	IP RATING	IP20 - FOR INDOOR USE ONLY	
	8W, 1070 LIVI, 3000K		CERTIFICATION	AU/NZ	AS/NZS 60598.1, 60598.2.1
DIMMING	220-240V REGION		CENTIFICATION	FU	EN 60598.1, 60598.2.1
	OPTIONS PHASE - DIMMING BANGE 5 - 100%			US/CAN	ETL/UL 1598, CSA C22.2#250.0
01 110110	DALI - DIMMING RANGE			00,0,4,	E 1 E 6 E 1666, 667 (6 E E E 17 E 6 6 16
			CORD	3M / 9'10" CLE	AR COAXIAL CABLE
	110-120V REGION				
	PHASE - DIMMING RANGE :	- DIMMING RANGE 3 - 100%		3000 / 9"0" X Ø1.2MM STAINLESS STEEL WIRE LONGER LENGTHS AVAILABLE UPON REQUEST	
	DALI - DIMMING RANGE 0.1 - 100%				
	ALL US AND CANADIAN ORDERS COME SUPPLIED WITH 120V COMPONENTRY CERTIFIED FOR USE IN THESE REGIONS. FOR OPTIMAL DIMMING PERFORMANCE WE RECOMMEND SOURCING A DIMMER CAPABLE OF SETTING THE DIMMING RANGE OF THE FIXTURE.		CANOPY	VARIOUS - SEE CANOPY OPTIONS ON FOLLOWING PAGE	
			SKU CODES	EG. MP.G-FCL.A-CHM	
				MENÉ PENDANT IN FROSTED CLEAR GLASS WITH A	
				CHAMPAGNE ANODISED BODY	
DDI) (ED 0175				MP.G-XXX.A-CH	IM MENÉ PENDANT
DRIVER SIZE	PHASE / TRIAC		FINIOUEO		
220 -240V	ALL MP - L101 X W51 X H29 / L4" X W2" X H1.1"		FINISHES GLASS	DI ACK (C DI IC	
			GLASS	BLACK (G-BLK) CLEAR (G-CLR)	
				FROSTED CLEAR (G-FCL)	
	ALL MP - L120 X W51 X H29 /	/ I / 7" Y W/2"/ Y H11"		FRUSTED CLEA	AN (G-PCL)
	ALL IVIP	L4./ A WZ / A I II.I	BODY	CHAMPAGNE A	NODISED (A-CHM)
110-120V	PHASE / TRIAC		ВОВТ	OTTAINIT AGINE A	INODICED (A CITIVI)
110 120 V	ALL MP - L75 X W35 X H26.5 / L3" X W1.4" X H1" DALI		PRODUCT		
			WEIGHT	10KG / 22LB	
	ALL MP - L75 X W35 X H26.5 / L3" X W1.4" X H1"		PACKAGING		
			DIMENSIONS L 530 W 530 H 450 / L 20.9" W 20.9" H 17.7"		
			PACKAGING		

DIMENSIONS



Ø440 H315 Ø17.3" H12.4"

AVAILABLE CANOPIES

ALL ROSS GARDAM CEILING MOUNTED FIXTURES COME SUPPLIED WITH A CEILING CANOPY UNLESS OTHERWISE SPECIFIED. EACH CANOPY INCLUDES ELECTRICAL CONNECTORS, EARTH WIRE AND CABLE RETENTION TO CONNECT TO MAINS POWER. THE BELOW IMAGES DEPICT THE CEILING CANOPIES AVAILABLE WITH EACH FIXTURE TYPE. IF NO CANOPY IS SELECTED, THE STANDARD CANOPY (NON US/CAN REGION) OR LARGE CANOPY (US/CAN) WILL BE SUPPLIED.



STANDARD SUSPENSION + COAXIAL CANOPY CAN.ST.120.CX.X-XXX

Ø120 X 30MM / 4.7" X 1.2" DRIVER HOUSED IN CEILING



SUSPENSION + COAXIAL CANOPY CAN.ST.170.CX.X-XXX

Ø170 X 40MM / 6.7" X 1.6" DRIVER HOUSED IN CANOPY



SLIM SUSPENSION + COAXIAL CANOPY CAN.SL.CX.X-XXX

Ø120 X 7MM / 4.7" X 0.3" DRIVER HOUSED IN CEILING



PUCK SUSPENSION + COAXIAL CANOPY CAN.PK.CX.X-XXX

Ø50 X 65MM / 2" X 2.6" DRIVER HOUSED IN CEILING

TECHNICAL

MATERIAL

CANOPY

ANODISED ALUMINIUM





ANODISED BLACK (A-BLK) ANODISED CHAMPAGNE (A-CHM)

SKU CODES EG. CAN.ST.120.CX.A-CHM =

STANDARD COAXIAL WITH SUSPENSION CANOPY IN CHAMPAGNE ANODISED FINISH







12KG / 26LB